

Graphite

Pencil drawings are one of the oldest forms of self-expression. A versatile medium, artists throughout the centuries have used charcoal to sketch the outlines of frescos, while others used the medium to create illustrated masterpieces. Lunada Bay Tile takes inspiration from this art form for its latest ceramic collection, Graphite. The subtly textured tile has the appearance of soft pencil or charcoal, evoking emotion and drama through its black iron shading.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

©2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application		Suitable		Interior	Exterior
Interior Wall/Backsplash		Yes	Shower	Yes	Yes
Fireplace/Cooktop Surround		Yes *	Steam Shower	Yes	N/A
Shower Wall		Yes	Light Residential	Yes	No
Steam Shower		Yes	Residential	No	No
Exterior Wall		Yes **	<i>DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 1371-2018</i>		
Pool, Spa or Water Feature (fully submerged)		Yes **			
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Piece)	Packaging (Per Box)	Standards Methods		
4" Hex	0.824 SF	5 Sheets/4.120 SF	Breaking Strength	ASTM C648	>450 PSI
2 1/2 x 9 1/2"	0.155 SF	32 Pcs/4.96 SF	Water Absorption	ASTM C373	Vitrous $\geq 0.5\%$ - $\leq 3.0\%$
3 1/2 x 9 1/2"	0.233 SF	20 Pcs/4.66 SF	Chemical Resistance	ASTM C650	Unaffected
Liner 3/4 x 9 1/2 x 1/2"	0.791 SF	80 Pcs/Box	Freeze/Thaw	ASTM C1026	Unaffected
			Thermal Shock	ASTM C484	$\pm 0.26\%$ / $\pm 1.5\text{mm}$
Shade Variation		Grout Joint Recommendation		NOTES	
V1 - V2 Slight Variation		1/8" (3 mm)		<p>Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).</p>	
MAINTENANCE					
A routine cleaning of tiles can be done with light duty, diluted close to neutral pH detergent cleaner or any non-abrasive cleaning solutions.					

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. Not recommended for placement inside a firebox.

** Acceptable for use or installation in pools, spas, or water features. Textured surface may require sealer and/or more frequent maintenance.

FLOOR APPLICATION DEFINITIONS:

LIGHT RESIDENTIAL - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

RESIDENTIAL - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.