

You journey the world to find it; the place where serenity joins exploration. Where the sea meets the sand and the cliffs meet the clouds, you find an untouched path that sparks transformation.

Tommy Bahama® calls this living the island life. The brand invites you to a place without deadlines or demands, to enjoy simple pleasures, and to live spontaneously — all while breathing freely and relaxing in style.

Lunada Bay Tile is pleased to partner with Tommy Bahama® to create a premier collection of tile. An exquisite collection of handcrafted glass tile blends inspired by the most exotic and untouched destinations of the world.

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.



Tommy Bahama® by **LUNADA BAY TILE**

Up to 70% post-consumer recycled glass content © 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	Yes	Yes **
Fireplace/Cooktop Surround	Yes *	Steam Shower	Yes **	N/A
Shower Wall	Yes	Light Residential	Yes	No
Steam Shower	Yes **	Residential	Yes	No
Exterior Wall	Yes	DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 137.1-2018		
Pool, Spa or Water Feature (fully submerged)	Yes **			

PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet)	Packaging (Per Box)			
1 x 1" Offset	1.07	5 Sheets/5.35 SF	Breaking Strength	ASTM C-648	> 350 PSI
1 x 2" Brick	1.00	5 Sheets/5.00 SF	Water Absorption	ASTM C-373	Impervious $\leq 0.5\%$
1/2 x 4" Brick	0.84	5 Sheets/4.20 SF	Chemical Resistance	ASTM C-650	Unaffected
1 x 4" Brick	0.85	5 Sheets/4.25 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Vineyard	0.82	5 Sheets/4.10 SF	Thermal Shock	ASTM C-483	Passed
Zig & Zag	0.74	5 Sheets/3.70 SF			

Shade Variation	Grout Joint Recommendation
V4 - Substantial Variation	1/16" (1.6 mm)

NOTES

Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. **Installation constitutes acceptance.** We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of Tommy Bahama Glass tiles can be done with light duty, diluted close to neutral pH cleaner.

* Acceptable for use near open flame or heat source; however, it is not considered 'Fire Glass'.
 ** ACCEPTABLE SIZES: 1 x 1", 1 x 2", and Vineyard Only. No other sizes are recommended.

FLOOR APPLICATION DEFINITIONS:
Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.
Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.